



**Sales Rep:** Chad Sienkiewicz  
**Estimate By:** Lam Pham  
**Finalized By:** Juan Jaime  
**Date:** 10/2/2025

**Customer:** ACH Homes LLC  
**Job Name:** 4024 85th Ave SE  
**Job Number:** J1183948F2  
**Plan:**

**Address:** 4024 85th Ave SE Mercer Island, WA 98040

**Drawing Type:** Roof Trusses  
**Loading**  
 TC/LL= 25.0 lb/ft<sup>2</sup>  
 TC/DL= 8.0 lb/ft<sup>2</sup>  
 BC/LL= 0.0 lb/ft<sup>2</sup>  
 BC/DL= 7.0 lb/ft<sup>2</sup>  
 WIND= 110 mph  
 EXP= SuburbanAreas

- THIS IS A TRUSS PLACEMENT PLAN ONLY. All trusses are designed as individual building components built to the building designer's specifications as given to us in the plans, see individual truss design sheets for specific loading and design.  
 - VERIFY ALL DIMENSIONS. Temporary truss bracing is the responsibility of the general contractor. Permanent bracing is the responsibility of the building designer. Individual bracing of "at-compression" truss pieces is marked out on the truss seals and it is the responsibility of the contractor to verify it is installed as specified.  
 - Do not install broken/damaged trusses or trusses that do not match the jobsite conditions, please inform your salesman if any such conditions are discovered.  
 - All Truss-To-Structural element connections shown on this layout are a suggestion provided as a courtesy to the builder and must be specified in the construction documents as approved by the building designer per ANS/ITP1 1-2014 2.3.2.4 prior to their installation.

**\*\* IMPORTANT \*\***

**▲ = INDICATES LEFT END**